


A person wearing a red life vest and dark shorts is jumping into a body of water with their arms raised in a 'V' shape. The background shows a blue sky with scattered white clouds and a green forested shoreline. The image is partially overlaid by a blue and white geometric shape on the left side.

What's New in HCL RTist 10.3

updated for sprint 2019.19

Overview

- ▶ RTist 10.3 is based on Eclipse Photon (4.8)
- ▶ HCL RTist is functionally equivalent and 100% compatible with IBM RSARTE.



HCL RealTime Software Tooling

Version: 10.3.0.v20190508_0600

Release: 2019.19

(c) Copyright IBM Corporation 2004, 2016. All rights reserved.

(c) Copyright HCL Technologies Ltd. 2016, 2019. All rights reserved.

Visit <https://www.hcltech.com/products-and-platforms/support>



Internal Transitions

- ▶ Internal transitions for the enclosing composite state can now be shown in a compartment beside the state chart diagram of the composite state.
- ▶ The transitions can be shown in columns to get a compact presentation



Rulers & Grid

Appearance

Advanced

Filtering


- Show Junction and Entry/Exit Point Names
- Show Choice Point Names
- Show State Names
- Show Transition Names
- Show Internal Transition Comments inside Compartment
- Show Transition Effects
- Show Transition and Trigger Guards
- Show Transition Events
- Show Trigger Parameters
- Show Trigger Ports

Enclosing State Internal Transitions

Show beside state diagram

Navigation in Hierarchical State Machines

- ▶ A transition path can now more easily be followed in a hierarchical state machine by means of the "Go Inside" and "Go Outside" commands
 - Select an entry/exit point before going outside to highlight the same entry/exit point in the enclosing state machine. And in the same way when following a transition path into a composite state.





Navigating to Diagrams in the Project Explorer

- ▶ Perform *Navigate – Project Explorer* in the background of a diagram to navigate to the diagram in the Project Explorer
 - Previously it was only possible to navigate to the model element owning the diagram
 - Navigating to diagrams from search results also work now


External Projects Import

- ▶ A new view makes it easier to import external projects into the workspace
- ▶ Define where to look for external projects and then import found projects easily into the workspace
- ▶ Now possible to specify the location of external projects with a file on the same format as is supported by the model compiler



External Projects Import

- ▶ Commands are available for working with the External Projects Import view using keybindings
 - Define your desired keybindings for the commands you want to use (there are no default keybindings for them)




The screenshot shows a window titled "external p" containing a table with the following columns: Command, Binding, When, Category, and User. The Category column has a dropdown menu open, showing "External Projects" selected for all listed commands.

| Command | Binding | When | Category | User |
|--------------------------------|---------|------|-------------------|------|
| External Projects Preferences | | | External Projects | |
| Import Selected | | | External Projects | |
| Refresh External Projects | | | External Projects | |
| Select All External Projects | | | External Projects | |
| Unselect All External Projects | | | External Projects | |

- ▶ The External Projects Import view can now be filtered using project paths
- ▶ Often the view is automatically updated when external projects change (can for example be caused by switching branch in Git). If not, you can use the Refresh External Projects to update the list of external projects.


Typedef Types

- ▶ The typedef implementation type is now shown in the Project Explorer, Properties view etc.
- ▶ The “Implementation Type” property is now accessible without scrolling in the Properties view




Properties View

- ▶ When a TC is selected information about the .tcjs file is now shown in the Properties view




Code Editing

- ▶ Some irrelevant code snippets are now hidden from the Code view
 - Constructor initializer for non-constructor operations
 - Body for interface operations and trigger operations
- ▶ Hidden code snippets can be made visible by means of the context menu



Transformation Configuration Editor

- ▶ Now supports the “Link with Editor” button of the Project Explorer



- ▶ Improved the command “Navigate to Inherited Value” so that it works in more situations



Transformation Configuration Editor

- ▶ If a TC contains anything but single and simple assignment of TC properties, only the Code tab can be shown
 - Other tabs are hidden since form-based editing is not possible in this case
- ▶ An annotation marker is shown in the ruler of the Code tab to pinpoint these JavaScript statements
 - Remove these statements to get back all tabs in the TC editor

```
9 tc.createTargetProject = true;
10x) tc.createTargetProject = false;
11 tc.targetProject = '/Course_target';
12 tc.compilationMakeCommand = 'mingw32-make';
13x) if (tc.createTargetProject)
14     tc.compilationMakeType = MakeType.MS_nmake;
15 tc.compileArguments = '${DEBUG_TAG}';
16x) JavaScript statement beyond simple assignment
17 tc.targetConfiguration = 'WinT.x64-VisualC++-15.0';
18 tc.targetServicesLibrary = 'D:\\git\\rsarte-target-rt\\r
19 tc.targetCpu = 'platform/resource/Course/CDDMod
20 <
```

Code

Access to Top-Level TC Properties from Prerequisite TCs

- ▶ A prerequisite TC can now access properties from the built TC (a.k.a. the “top-level TC”)
- ▶ This is useful when creating libraries to be built in many different contexts

For example:

```
let tc = TCF.define(TCF.CPP_TRANSFORM);
```

```
let topTC = TCF.getRootTransformationConfiguration();
```


```
tc.targetConfiguration = topTC.targetConfiguration || 'WinT.x64-VisualC++-15.0';
```

Enable Support for File Artifacts


- ▶ The TC property “Enable Support for file artifacts” has been removed
- ▶ File artifacts will be translated to C++ if they are present among the source elements (i.e. they are now handled in the same way as all other kinds of model elements)

Model Compiler

- ▶ Support for automatic detection of source dependencies
 - The Sources list of the built TC can be dynamically extended to include all elements that are referenced (directly or indirectly) from built elements



- ▶ The location of the model compiler is now shown in the Preference page
 - Makes it easier to run it from the command line



Model Compiler

- ▶ A new script in <install dir>/rsa_rt/tools/ makes it easier to launch the model compiler
 - No longer necessary to find the location of the containing plugin
- ▶ Running the model compiler with no command-line arguments will now show its help
- ▶ Make is now always run as part of building (it will detect whether something needs to be built or not)
- ▶ There are new preferences for the build server (i.e. the a model compiler running in server mode)
 - It can now be disabled, so it isn't automatically launched at start-up (useful in case no build features are used)
 - A new button for opening the build server log (helps troubleshooting)
 - A new preference for automatically restarting the build server when it has been idle for a certain time

Build Server

Launch build server at start-up

VM arguments: -Xverify:none -Xmx4024m

Port range (syntax is lower:upper), restart is required : 61004:61020



Status: server is running at port 61004

Restart Server Log

Restart build server on idle time (in mins) 30

Model Compiler

- ▶ It's no longer necessary to specify a license when launching the model compiler from command-line
 - The license of the RTist installation will be used
- ▶ Multiple TCs can now be built in one go
 - Select all TCs to build in the UI and perform the Build context menu command
 - The selected TCs will be built one by one consecutively



Model Compiler

- ▶ Environment variables can now be used in the "Build folder" of an external library TC
- ▶ Build variant scripts can now update TC prerequisites during the build. Also, there are now error messages printed if a build variant script tries to modify any TC properties that are not allowed to be modified (e.g. Type or Parents).

Code Analysis


- ▶ Generated CDT projects are now set-up to use CDT GCC Built-in Compiler settings
 - Makes code analysis work better

```
14:19:58 : INFO : Generating XML file with CDT projects info...
```

```
14:19:58 : INFO : CDT GCC Built-in Compiler Settings provider will be applied to generated target projects for Code Analysis support
```


```
14:19:59 : INFO : Generating XML file with CDT projects info... Done
```

- Disable this in Preferences if not using a GNU compiler (*RealTime Development – Build/Transformations – C++ - Generate additional information for Code Analysis*)
- Note: When this preference is changed all target projects should be removed. A dialog appears to do this automatically.




Model Debugger

- ▶ The Debug view now shows more clearly when the top capsule has not yet been incarnated
 - Also, ports for the top capsule are not shown until it has been incarnated



- ▶ “Type-wide” breakpoints are now supported
 - Breakpoints set before starting a model debug session applies to all instances of a capsule (“type-wide”)
 - In an instance diagram you can now choose if a breakpoint should be “type-wide” or only apply on that particular instance



Model Debugger


- ▶ Breakpoints are now more clearly described in the Breakpoints view
 - Distinction between “type-wide” and instance breakpoints



- ▶ In-line editing of data for an event in the Events view is now supported
 - Only use the browse (...) button when entering data spanning over multiple lines


| | | |
|----------------|------|---|
| yellow | void | |
| createInstance | int | 1 |
| setTimer | int | 1 |

- ▶ The number of instances in a capsule part are now shown in the Debug view
 - A special icon is used to denote empty capsule parts




Model Debugger

- ▶ Instance diagram labels are more compact now
 - Shows the launch configuration name (by default named as the TC) and the instance path



- ▶ Event queues are now shown in the Debug view. Under each port instance you can see the events waiting to be dispatched to that particular port instance.
 - The event priority and data (if any) is shown



- ▶ The Variables view now shows also private inherited attributes of a capsule instance

External Port Data

- ▶ The TargetRTS implementation of external ports has been extended to make it easier for code running in an external thread to pass data to an RTist application thread.

- Data can now be passed when raising an external event

```
// This function may be used only on threads other than the one on
// which the owner capsule executes. Data can optionally be included in the request.
// After calling this the owner capsule is automatically disabled from receiving another 'raise'
// request until 'enable' is called again.
int raise(const void * data = 0, const RTObject_class * type = 0);
```


- A thread-safe shared data area (a list) also exists on the external port itself

```
// Put a data object at the end of the externalData list. The data object should be non-null and dynamically allocated by
// code in the external thread, which calls this function.
void dataPushBack(void*);

// Pops the front data object off the externalData list. Returns the number of remaining data objects in the list
// (the data will be null in case of error, for example when attempting to pop from an empty list).
// This function is usually called by the owner capsule thread, and it should delete the popped data object when done with it.
unsigned int dataPopFront(void**);


// Pops the back data object off the externalData list. Returns the number of remaining data objects in the list
// (the data will be null in case of error, for example when attempting to pop from an empty list).
// This function is usually called by the owner capsule thread, and it should delete the popped data object when done with it.
unsigned int dataPopBack(void**);

// Attempts to find a specific data object in the externalData list. If it is found it will be deleted.
void dataDelete(void*);
```




GitHub Repositories

- ▶ A number of RTist sample applications have been created on GitHub
 - Focus is to show various ways how to send messages to or from a generated C++ application
- ▶ Also used for providing libraries of reusable functionality
- ▶ Repositories are located in the <https://github.com/hcl-pnp-rtist> organization and are MIT licensed
- ▶ Pull requests are welcome



JSON API for External Communication with RTist Applications


- ▶ [lib-tcp-server](#) is a library that allows an RTist application to communicate with other applications over TCP
 - Provides a JSON-based API for sending and invoking events on certain ports
 - Outgoing events on those ports can be routed to an external application
 - Available on GitHub as an open-source library
- ▶ The API can be used for developing distributed applications
 - A light-weight alternative to using Connexis
 - [pingpong-distributed](#) is a sample distributed application built this way
- ▶ The API can also be used as a way to test applications (black-box testing)



```
{ "command": "sendEvent", "port" : "trafficLight", "event" : "test_int", "data" : "int 15" }
```

TargetRTS Documentation

- ▶ The most commonly used classes and functions in the TargetRTS are now documented using Doxygen comments
- ▶ Generated Doxygen documentation is included in the Help
- ▶ This documentation is also useful when editing or viewing code in the Code editor



The screenshot shows a code editor with several tabs: Initial, RTActor.inl, RTActor.h, RTController.h, and Cap.cpp. The main window displays C++ code with a tooltip for the `perror` function. The code in the editor is:

```
30 printf("Cap instance started at index %d", getIndex());  
31 RTController* controller = context();  
32 controller->perror("An error occurred");|
```

The tooltip for `perror` contains the following text:


```
/* Print an error message to stderr. The printed messages will consist of a prefix followed  
by the message of the most recent error that occurred in the controller's thread.  
@param s A string that will precede the error message.  
*/  
void                perror( const char * s = "error" );
```

At the bottom right of the tooltip, it says "Press 'F2' for focus".


- Note that the Code view does not support showing these tooltips

Searchable API Documentation

- ▶ Both the C++ TargetRTS APIs and JavaScript APIs are now searchable from the Help




The screenshot shows a web browser window with the title 'Help'. The navigation bar includes 'Contents', 'Search', 'Related Topics', 'Bookmarks', and 'Index'. The search bar contains the text 'incarnate' and a 'Go' button. Below the search bar, the scope is set to 'Default'. The search results are categorized under 'Local Help (1-10 of 14 hits)'. The first result is 'C++ TargetRTS: Frame::Base Class Reference', which includes a description of public member functions and attributes. The second result is 'C++ TargetRTS: RTFrame.h Source File', which includes copyright information for HCL and IBM.



The screenshot shows a web browser window with the title 'Help'. The navigation bar includes 'Contents', 'Search', 'Related Topics', 'Bookmarks', and 'Index'. The search bar contains the text 'initBuildVariants' and a 'Go' button. Below the search bar, the scope is set to 'Default'. The search results are categorized under 'Local Help (5 hits)'. The first result is 'JSDoc: Home', which lists various namespaces and methods. The second result is 'JSDoc: Namespace: BVF', which describes a 'Build Variant Framework' object and its methods.

Online Documentation

- ▶ The RTist Eclipse Help documentation is now also available on: <https://rtist.hcldoc.com/help/index.jsp>
- ▶ This documentation is now tagged to enable search engines to index the contents



HCL

*Relationship*TM
BEYOND THE CONTRACT

\$7 BILLION ENTERPRISE | 110,000 IDEAPRENEURS | 31 COUNTRIES

 WATCH THE FILM